Lucas

Lucas Diesel Systems

MULTIBRAND CALIBRATION

COMMON RAIL INJECTORS PIEZO COMMON RAIL INJECTORS HEUI INJECTORS



EDR 720

MANUAL GAUGE FOR THE CALIBRATION OF DIESEL INJECTORS

lucasdiesel.com

Trust Lucas

Lucas

EDR 720

MANUAL GAUGE FOR THE CALIBRATION OF ALL BRANDS OF DIESEL INJECTORS



The technological design of this EDR 720 manual calibration gauging system enables the precise adjustment of any BOSCH, VDO, DENSO and CAT Common Rail injector. After the gauging process, the diesel specialist can **assemble the Common Rail injector** secure in the knowledge that the configuration of such is perfect, which guarantees subsequent performance of the injector on the test bench, always in accordance with the original manufacturer values.

Thanks to the ongoing development of new configuration records for all of the systems and the generation of **new accessories,** the **EDR 720** is equipped to meet any market requirements, and the new records can be directly updated online using the gauge software.

In addition with an **easy to use**, intuitive, interactive and dynamic system, the diesel specialist can calibrate the components in the most efficient manner, therefore gaining a lot of profitability for your business.



EDR 720 - LDFT0374

EQUIPMENT COMPOSITION

EQUIPMENT Select one of the following

REF.	
LDFT1129	BOSCH CRIN & CRI INJECTORS APP
LDFT0375	DENSO CRIN & CRI INJECTORS APP
LDFT0377	HEUI C7 - C9 CAT - FORD INJECTORS APP

ACCESSORIES

REF.	
LDFT1129	BOSCH CRIN & CRI INJECTORS APP
LDFT0375	DENSO INJECTORS APP
LDFT0377	HEUI C7 - C9 CAT - NAVISTAR INJECTORS APP
LDFT1134	6.4 - 6.6 PERKINS/CAT INJECTORS APP
LDFT0376	SIEMENS/VDO INJECTORS APP
LDFT0379	SPRING-LOADED GAUGE FOR COMMON RAIL
LDFT0378	BOSCH LIFT DETECTOR 3° STEP FOR CR INJECTORS

TECHNICAL SPECIFICATIONS

GAUGING SYSTEM	
GAUGE CALCULATION	 Armature stroke Armature stroke air gap Nozzle needle lift Valve spring force (only with the optional P.N. LDFT0379) Nozzle spring force (only with the optional P.N. LDFT0379)

DIMENSIONS	
HEIGHT	320 mm
WIDTH	320 mm
DEPTH	290 mm
VOLUME	0.025 m ³
WEIGHT	20 kg

I.T. SYSTEM		IN
OPERATING SYSTEM	PC not included	м
SOFTWARE	• HUMMINGBIRD	TE
		U
		sc
		IN

INFORMATION SYSTEMS	
MULTIBRAND	All brands
TEST RECORDS	 Available for BOSCH CR CRIN & CRI Available for DENSO CR CRI Available for SIEMENS CR
UPDATING	Permanent over the internet
SOURCES	Original specifications of the automobile manufacturers
INFORMATION	 Insulation tests Coil resistance tests Tightening parameters to correctly adjust each part of the injector There is no need to dismantle the injector again after the bench tests

APPLICATIONS





HEAVY COMMERCIAL



AGRICULTURAL

EUROPE

UK - Chichester Road - Ponswood Ind. Estate TN38 9BG - ST Leonards-On-Sea - East Sussex

SPAIN - Pol. Ind. Morea Sur, 59 - 31191 Beriain - Navarre

ITALY - Via F. Filzi, 15 - 20032 Cormano - Milan

NORTH AMERICA

USA - Southfield Town Center - 1000 Town Center - Suite 725 48075 Southfield - Detroit - Michigan

CENTRAL AMERICA

PANAMA - Boulevard Costa del Este Financial Park Tower - Planta 20 - Costa del Este - Panama City

SOUTH AMERICA

BRAZIL - Rua Gastão Vidigal, 370 -13570-655 - São Carlos - SP



Trust Lucas